

Cost contingency is an amount of money set aside to cover uncertainties or unexpected costs associated with a project. These unexpected costs can be due to a variety of factors such as design changes, price inflation, labor issues, or unanticipated technical challenges. The purpose of including a cost contingency in a budget is to prepare for risks and to improve the likelihood that the project will be completed within budget. Here are some common methods for calculating cost contingency:

### 1. Percentage of Total Estimated Cost

This is the simplest method where a fixed percentage (often between 5% to 20%, depending on the nature of the project and its associated risks) is added to the total estimated project costs. For example, if the estimated cost of a project is \$100,000 and a 10% contingency is applied, then the contingency amount would be \$10,000.

### 2. Expert Judgment

This method involves consulting experts familiar with similar projects. They provide their assessment of what level of contingency is appropriate, based on their past experience and knowledge.

### 3. Risk Analysis

This is a more sophisticated approach that involves the identification and assessment of individual project risks. Each risk is estimated for its potential cost impact and likelihood of occurrence. The contingency amount is then calculated by summing up the expected values of all identified risks.

For example:

Risk A has a 10% chance of occurring and could cost \$5,000:  $0.1 * \$5,000 = \$500$

Risk B has a 20% chance of occurring and could cost \$2,000:  $0.2 * \$2,000 = \$400$

Risk C has a 5% chance of occurring and could cost \$10,000:  $0.05 * \$10,000 = \$500$

The total contingency would then be  $\$500 + \$400 + \$500 = \$1,400$

#### 4. Historical Data

This involves looking at similar past projects and determining the actual amount by which costs exceeded initial estimates. This historical percentage or amount is then applied to the new project.

#### 5. Monte Carlo Simulation

This is a statistical technique that allows for a range of outcomes to be modeled by inputting a range of values for uncertain variables. The result is a distribution of possible total project costs, from which a contingency can be derived.

#### 6. Hybrid Approaches

Many organizations use a combination of these methods to calculate contingency. For example, a basic percentage may be applied, and then additional amounts added for specific known risks that have been individually assessed.

# ProjectCubicle

#### Considerations

Cost contingency is often revisited and revised as the project progresses and more information becomes available.

The contingency should be clearly documented, including the methodology used for its calculation and the assumptions made.

It's important to note that cost contingency is different from management reserves.

While contingency is meant for identified but uncertain costs, management reserves are set aside for unidentified or "unknown-unknown" issues that might arise during the project.

## Example Project

Suppose we are working on a construction project with the following estimated costs:

Labor: \$50,000

Materials: \$30,000

Equipment: \$20,000

Total Estimated Cost = Labor + Materials + Equipment

Total Estimated Cost = \$50,000 + \$30,000 + \$20,000 = \$100,000

### 1. Percentage of Total Estimated Cost

If we use a fixed percentage of 10% for contingency, the calculation is straightforward.

Contingency = 10% of \$100,000

Contingency = \$10,000

### 2. Expert Judgment

Suppose an expert suggests that a contingency of \$8,000 would be sufficient based on their experience. In this case, you would directly use this figure as your contingency.

Contingency = \$8,000

### 3. Risk Analysis

Let's identify three risks:

Risk A: Design changes (10% likelihood, \$5,000 impact)

Risk B: Price inflation (20% likelihood, \$2,000 impact)

Risk C: Labor strikes (5% likelihood, \$10,000 impact)

For each risk, we calculate the expected value as follows:

Expected Value (Risk A) =  $0.10 * \$5,000 = \$500$

Expected Value (Risk B) =  $0.20 * \$2,000 = \$400$

Expected Value (Risk C) =  $0.05 * \$10,000 = \$500$

Total Contingency = Sum of Expected Values

Total Contingency =  $\$500$  (Risk A) +  $\$400$  (Risk B) +  $\$500$  (Risk C) =  $\$1,400$

#### 4. Historical Data

If historical projects have shown that the final cost is generally 7% higher than the initial estimates, we would apply this rate:

Contingency = 7% of  $\$100,000$

Contingency =  $\$7,000$

#### 5. Monte Carlo Simulation

This would involve specialized software and is beyond simple calculations, but the outcome would be a range or distribution for the contingency amount based on numerous simulations.

#### 6. Hybrid Approach

We could use a percentage approach for base costs and add the result of the risk analysis:

Base Contingency = 5% of  $\$100,000 = \$5,000$

Risk-based Contingency =  $\$1,400$  (from Risk Analysis)

Total Contingency =  $\$5,000$  (Base) +  $\$1,400$  (Risk) =  $\$6,400$